

# Modular hydrogen refueling station

## For heavy-duty vehicles 700 & 350 bar



With more than 200 hydrogen stations delivered all over the world, Air Liquide provides **global hydrogen refueling solutions** from project definition to operation and maintenance support.

Part of the modular refueling station product line, the station dedicated to heavy-duty vehicles can supply gaseous hydrogen at **700 & 350 bar** dispensed through a safe protocol for fast refueling.

The modularity of the station enables support different layouts and use cases with a capacity from **1 to 4 ton per day**.

## Key benefits

- ✓ Modularity and upgradable concept
- ✓ Up to 4 parallel fillings and up to 72 HDV within a day
- ✓ Low GWP cooling system
- ✓ Reliability proven by endurance tests
- ✓ Optimised TCO for 700 bar applications
- ✓ More than 100 patents



**ALL-IN-ONE**  
For light-duty vehicles




**MODULAR**  
From light-duty  
to heavy-duty vehicles



**MODULAR**  
For heavy-duty vehicles 350 bar  
For heavy-duty vehicles 700 & 350 bar

# Modular hydrogen refueling station


Gas-to-gas series | For heavy-duty vehicles 700 & 350 bar



## Performances

Source: trailers	Entry configuration	Medium configuration	Extended configuration
Dispenser(s)	1 x H70/H35	2 x H70/H35	4 x H70/H35
Max. vehicles in 1 hour	5 vehicles (40 kg each)	8 vehicles (40 kg each)	11 vehicles (40 kg each)
24h capacity	1,400 kg/day	2,600 kg/day	3,800 kg/day

### Technical area\*



\* Source trailers and dispensers excluded.

## Technical specifications

<b>Fueling time</b>	<ul style="list-style-type: none"> <li>H35 - heavy-duty: 20 kg in 5 min</li> <li>H70 - heavy-duty: 40 kg in 7 min 60 kg in 10 min 80 kg in 14 min</li> </ul>
<b>Minimum inlet pressure</b>	<ul style="list-style-type: none"> <li>Trailers: 50 bar</li> <li>Electrolyzers, pipeline: 30 bar</li> </ul>
<b>Noise</b>	< 85 dBA at 1 m
<b>Utilities</b>	<ul style="list-style-type: none"> <li>400 V, 3 phases, 50 Hz, 450 to 1,000 kVA</li> <li>Compressed air system included</li> <li>Nitrogen for maintenance purposes only</li> </ul>
<b>Safety</b>	<ul style="list-style-type: none"> <li>Hydrogen / flame detection</li> <li>Emergency stop buttons</li> <li>Flare adapted to urban use</li> </ul>
<b>Environment</b>	Ambient operating temperature: -20°C to +40°C
<b>Codes and standard</b>	<ul style="list-style-type: none"> <li>CE marking - EN17127 - EN17268</li> <li>ISO 19880-1 + SAT tests certified by 3<sup>rd</sup> party (CEP)</li> <li>IR communication: SAE TIR J2799</li> <li>Metrology : OIML R139 - Certification by 3<sup>rd</sup> party</li> </ul>

## Modularity

### Compatible hydrogen sources

- Gas trailer and ground storage - possible source in parallel
- Pipeline or electrolyzers

### Compression and storage

- Number of compressors and MP/HP storage capacity upon request
- 98% availability - higher level of redundancy upon request

### Dispensers

- Up to 4 dispensers per station
- Parallel refuellings possible
- Adaptable branding and colors

## Services & maintenance support

- Preventive and corrective maintenance contract
- Technical assistance and training
- Spare parts supply
- Remote control for operation and assistance

## Contacts

### Air Liquide

2, rue de Clémencière  
BP 15 - 38360 Sassenage, France  
E-mail: ww-h2refuelingstations@airliquide.com  
www.advancedtech.airliquide.com

[www.airliquide.com](http://www.airliquide.com)



A world leader in gases, technologies and services for Industry and Health, Air Liquide is present in 73 countries with approximately 67,100 employees and serves more than 3.9 million customers and patients.